

Portable Eyewash

WG6000A / WG6000B

Portable Eye Wash Station

- It adopts PE materials, and the production materials comply with the regulations of F.D.A on the grade on PE materials for food (F.D.A. Regulation on Polypropylene: the requirements of U.S.21 CFR F.D.A. Regulation Part 177.1520, portable containers clauses (C) for food contact use), and it is superior in its high intensity, good toughness, good Rigidity, heat and cold resistance
- It complies with human engineering principle in design, and adopts the law of gravity to produce water pressure and deliver water to two nozzles for eye washing
- It applies to work places without water supply and discharge facilities and can be installed and fixed onto walls as required to provide timely and professional protection
- It complies with regulations of ANSI/ISEA on emergency eye wash station and showering equipment-ANSI Z358.1-2014
- It is suggested to discharge the liquid in eye wash station every two or four weeks or as required and clean every component of eye wash station




WG6000B

WG6000A



Long flushing time above ANSI standard.



Pull the rubber cover for immediate washing.



Easily discharge water in tank with the drainage hole at the base.



Able to be hanged on the wall, space saving.

Portable Eye Wash Station

Product	Main Material	Water Capacity (L/Gal)	Flow Speed (L/min)	Flushing Time (min)	Ext. size HxWxD(mm)	Packing size HxWxD(mm)	G.W. (kgs.)	N.W. (kgs.)	Certification	Model
Portable Eyewash (Type A)	PE	60/16	2.6	18	735x420x416	436x750x435	9.5	8.5	ANSI Z358.1 AS 4775 CE	WG6000A
Portable Eyewash (Type B)		30/8	2.6	9	625x350x342	357x635x360	7	6		WG6000B

WG6000AC / WG6000BC**Portable Eyewash with Cart**

- It consists of WG6000A and cart with waste water collection barrel
- It adopts the law of gravity to produce water pressure and deliver water to two nozzles for eye washing
- It applies to work places without water supply and discharge facilities, without installation requirements. The cart is equipped to facilitate moving and convenient professional emergency protection; it can also be installed and fixed onto wall
- It complies with regulations of ANSI/ISEA on emergency eye wash station and showering equipment-ANSI Z358.1-2014

**WG6000AC****WG6000BC****WG004****Portable Eyewash with Cart**

Product	Water Capacity (L/Gal)	Flow Speed (L/min)	Flushing Time (min)	Accessory Products Ext. size: HxWxD(mm)	Accessory Products Packing size: HxWxD(mm)	G.W. (kgs.)	N.W. (kgs.)	Certification	Model
Portable Eyewash(Type A)	60/16	2.6	18	WG6000A: 735x420x416	WG6000A: 436x750x435	38	35.3	ANSI Z358.1 AS 4775 CE	WG6000AC
				WG004: 1700x650x500	WG004: 250x665x525				
Portable Eyewash(Type B)	30/8	2.6	9	WG6000B: 625x350x342	WG6000B: 357x635x360	35.5	32.8		WG6000BC
				WG004: 1700x650x500	WG004: 250x665x525				
				WG6001D: 615x400x400	WG6001D: 640x580x510				

Accessories

Product	Main Material	Water Capacity (L/Gal)	Ext. size HxWxD(mm)	Packing size HxWxD(mm)	G.W. (kgs.)	N.W. (kgs.)	Model
Portable Eyewash Cart	Steel	-	1700x650x500	250x665x525	25	24	WG004
Portable Eyewash Waste Pail	PP	80/21	615x400x400	640x580x510	3.5	2.8	WG6001D